

Specifications.

Operating Speeds	Production speeds are, of course, contingent upon the nature of the work run, board, window material, etc.						ELECTRICAL	Main drive 5 HP, DC, 230 V, 50/60 HZ, 1 ϕ Apron vacuum cage motor & blower-2 (one/cage) 2 HP, AC, 230/460 V, 60 HZ, 3 ϕ Vacuum cylinder motor & blower 5 HP, AC, 230/460 V, 60 HZ, 3 ϕ Electronic trip AC, 115V, 1 ϕ Motor & pump for optional vacuum feed 2 HP, AC, 230/460 V, 60 HZ, 3 ϕ				
	Single Lane		Two Lanes		Three Lanes (Optional)							
	One up	100/min.	One Up	200/min.	One up	300/min.						
Two up	200/min.	Two up	400/min.	Two up	600/min.							
Three up	300/min.	Three up	600/min.	Three up	900/min.							
Shipping	DOMESTIC CRATED					CONTAINER SKIDDED						
	LENGTH	WIDTH	HEIGHT	VOLUME	WT.	LENGTH	WIDTH	HEIGHT	VOLUME	WT.		
	Feed (combing or suction)	7' 2.13m	5' 8" 1.73m	5' 9" 1.75m	228.1 cu. ft. 6.46 cu. m.	2570 lbs. 1165.8 kg.	Feed (combing or suction)	7' 2.13m	5' 4" 1.63m	5' 3" 1.60m	196 cu. ft. 5.55 cu. m.	3300 lbs. 1496.9 kg.
	Combiner	7' 2.13m	6' 3" 1.91m	6' 2" 1.88m	269.8 cu. ft. 7.64 cu. m.	5040 lbs. 2286.1 kg.	Combiner	7' 2.13m	5' 8" 1.73m	6' 1.83m	238 cu. ft. 6.74 cu. m.	5200 lbs. 2358.7 kg.
	Stacker (8CH)	7' 2.13m	6' 4" 1.93m	5' 1.52m	221.7 cu. ft. 6.28 cu. m.	900 lbs. 408.2 kg.	Stacker 8CH	7' 2.13m	6' 1.83m	5' 1.52m	210 cu. ft. 5.95 cu. m.	1000 lbs. 453.6 kg.

Floor Plan.

